



Fork-lift truck compatible with various load carriers. Useful for picking or moving goods in all types of warehouses and factories. The truck's light weight makes it ideal on surfaces such as mezzanine floors.

PALLET HANDLING

Light fork-lift truck for pallet transport, with a quiet, reliable lift for handling loads up to 500 kg.

APPLICATION AREAS

Ideal for clean environments (no hydraulics) and on mezzanine floors (light weight). Width 860 mm.

FLOOR REQUIREMENTS

No formal requirements, except that the floor should be even. Fork-lift truck 607 is suitable for mezzanine floors because of its low wheel pressure.

DIMENSIONS AND TECHNICAL INFORMATION

Performance

Maximum speed	4 to 10.5 kph (depending on load capacity)
Pulling capacity	500 kg
Maximum gradient	10%

Dimensions and weight

Weight incl. batteries	260 kg
Length	2200 mm
Width	860 mm
Height	1100 mm
Step-in threshold height	65 mm
Road clearance	3925 mm
Axle distance	1100 mm

Batteries

Batteries can discharge 75 to 80%. Fully discharged batteries have a voltage of 1.7V per cell or a total of 20.4V over all 12 cells.

Voltage	Capacity	Weight	Size (LxWxH)
12 V	50 Ah/5 h	20 kg	278x171x190 mm
12 V	70 Ah/5 h	30 kg	330x171x235 mm

Engine

Electrical system	24V AC
Power output	600 W
Engine type	In-wheel drive, AC

Wheel

Drive wheels	230x55 mm
Fork wheels	85x70 mm

Engeltron trucks are CE marked and are partly certified by DLR (Deutscher Lastkraftwagen-Verband) in the with Forklift.

We reserve the right to make technical changes without prior notice.



Unit F1, Maynooth Business Campus
Maynooth Co Kildare, Ireland
Tel: +(353) 1 6016106 | Fax: +(353) 1 6016109
e-mail: info@liftrite.ie | web: www.liftrite.ie