



APPLICATION AREAS

Light weight and compact external dimensions give this truck excellent manoeuvrability in narrow aisles and on mezzanine floors where traditional trucks are too heavy to use. The Ergobjörn concept is commonly used for picking small, lightweight items. This line of trucks is ideal for companies that handle light, non-bulky goods, such as 3rd party logistics, mail order, electronics, pharmaceutical and wholesale companies, as well as companies with long transport distances between warehouse and production facilities. Other application areas include hospitals, porter's offices, airports and staff transport over long distances.

PICKING

A unique docking system allows great flexibility as load carriers can easily be adapted to the conditions and requirements at hand. Several different load carrier types can be used with a single truck, so one truck can perform a variety of jobs during a working day. Easy connection and disconnection of load carriers and short distance between the truck and load carrier offers ergonomic and time benefits during picking.

Under the "Load carriers" tab above is a complete list of load carriers compatible with picking truck 612.

FLOOR REQUIREMENTS

No formal requirements, except that the floor should be even. Picking truck 612 is suitable for use on mezzanine floors.

Designed for handling and transporting light goods up to 500 kg. 1110 mm wide truck for hitching of 1000 mm wide load carrier. Ideal for use in narrow aisles where the driver picks items directly from the truck. Space for accessories on both sides of the drive unit. A unique docking system allows easy connection and disconnection of load carriers and enables several different load carrier types be used with the same truck. The load carriers are available in several lengths and designs, and are easy to customise.

DIMENSIONS AND TECHNICAL INFORMATION

Performance

Maximum speed	4 to 10.5 kph (depending on load capacity)
Pulling capacity	500 kg
Maximum gradient	10%

Dimension och vikt

Dimensions and weight	255 kg
Length	1450 mm
Width	1110 mm
Height	1100 mm
Step in threshold height	65 mm
Road clearance	30 mm
Axle distance	980 mm

Batteries

Batteries can discharge 75 to 80%. Fully discharged batteries have a voltage of 1.7V per cell or a total of 20.4V over all 12 cells.

Voltage	Capacity	Weight	Size (LxWxH)
12 V	50 Ah/5 h	25 kg	270x170x190 mm
12 V	30 Ah/5 h	16 kg	330x170x235 mm

Engine

Electrical system	24 V (AC)
Power output	600 W
Engine type	In-wheel-drive, AC

Wheels

Drive wheels	230x55 mm
Back wheels	200x50 mm

Aisle width requirements

Reversible without load carrier in shelf aisles	2000 mm
Reversible with load carrier 1000x800 mm in shelf aisles	2000 mm
Smallest suitable aisle width for driving and picking	1300 mm
Main aisle width for driving in and out in side aisles with load carrier 1000x800 mm	2000 mm

Figures include air conditioner and are partly certified by GHP (Swedish Machinery Testing Institute) in the side function.

We reserve the right to make technical changes without prior notice.



Unit F1, Maynooth Business Campus
Maynooth Co Kildare, Ireland
Tel: +(353) 1 6016106 | Fax: +(353) 1 6016109
e-mail: info@liftrite.ie | web: www.liftrite.ie